


PC-160205 Series

OUTLINE DIMENSION



MECHANICAL DIMENSION

Overall Dimension (mm)	122.0 X 44.0 X 10.0/13.0/13.5
Viewing Area (mm)	99.0 X 25.0
Format	2 lines X 16 Characters
Dot Size (mm)	0.92 X 1.10
Dot Pitch (mm)	0.98 X 1.16

ABSOLUTE MAXIMUM RATINGS


Parameter	Symbol	MIN	MAX	Unit
Supply Voltage for Logic	Vdd-Vss	-0.3	+7.0	V
Supply Voltage for LCD	Vlcd	Vdd - 12.0	Vdd + 0.3	V
Input Voltage	Vin	-0.3	Vdd + 0.3	V

ELECTRICAL CHARACTERISTICS (VDD=5.0V ; Top=25° C)

Parameter	Symbol	MIN	Typical	MAX	Unit
Power Supply Voltage	Vdd-Vss		5.0		V
LCD Operating Voltage	Vop		4.5		V
LCM Current Consumption	Idd				mA
Backlight Current Consumption	LED (Edge)				mA
	LED (Array)			280	mA
Driving Method		1/16 Duty 1/5 Bias			

NOTES

IC Controller / Driver: SPLC780D Or Equivalent
LCD Options: TN,FSTN,Grey STN,Y/G STN,Blue STN
Backlight Options: None,White LED,Yellow-Green LED,Green LED
Viewing Angle Options : 6:00,12:00
Operating Temperature Options: 0° C - +50° C,-20° C - +70° C
Storage Temperature Options: -10° C - +60° C,-30° C - +80° C



Dot Size

PIN ASSIGMENT

Pin No.	Symbol	Function
1	LEDK	Power Supply for LED B/L (-)
2	LEDA	Power Supply for LED B/L (+)
3	VSS	Power Supply (GND)
4	VDD	Power Supply (+)
5	V0	Contrast Adjust
6	RS	Register select signal
7	R/W	Data Read / write
8	E	Enable Signal
9	DB0	Data Bus Line
10	DB1	Data Bus Line
11	DB2	Data Bus Line
12	DB3	Data Bus Line
13	DB4	Data Bus Line
14	DB5	Data Bus Line
15	DB6	Data Bus Line
16	DB7	Data Bus Line