



CH1 PIN.

PIN NO.	PIN NAME
1	VDD
2	VDD
3	VSS
4	REV
5	Rin1-
6	Rin1+
7	VSS
8	Rin2-
9	Rin2+
10	VSS
11	Rin3-
12	Rin3+
13	VSS
14	ClkIN-
15	ClkIN+
16	GND
17	Rin4-
18	Rin4+
19	VSS
20	NC

CH2 PIN.

PIN NO.	PIN NAME
1	Vcc
2	GND
3	Enable
4	Dimming
5	NC

1	Operating Voltage:	Vdd=3.3V typ.
2	Resolution:	1024RGB*768
3	Color:	16.2M
4	Interface:	LVDS
5	Viewing Direction:	6:00
6	Operating Temp:	-20°C~70°C
7	Storage Temp:	-30°C~80°C

REVISION										DRAWN BY Zhixing,Xu		UNLESS OTHERWISE SPECIFIED:		POLYTRONIX, INC.		805 ALPHA DRIVE	
REV	ECO NO	DESCRIPTION	DWN	DATE	CHKD	DATE	APVD	DATE	APVD	DATE	DATE: Feb/27/2015	1) ALL DIMENSIONS ARE IN MM.		RICHARDSON, TX 75081		972.238.7045	
A		Initial		Feb/27/2015							CHECKED BY	2) TOLERANCE		CUSTOMER ID NUMBER:		SHEET 1_OF_1	
											DATE:	.XXX ±.127		THIRD ANGLE PROJECTION		TITLE:	
											APPROVED BY	.XX ±.254		DRAWING SCALE:		CAGE CODE NO. POLYTRONIX PART NUMBER:	
											DATE:	ANGLES ±0.5°		NONE		2Y126 PT-150XG-NN-01	
											APPROVED BY	DO NOT SCALE DRAWING		REV.:		A	
											DATE:						